









DRZWI DREWNIANYCH																
	D1Z <small>drzwi zewnętrzne</small>		D2Z <small>drzwi zewnętrzne</small>		D1 <small>drzwi wewnętrzne</small>		D2 <small>drzwi wewnętrzne</small>		D3 <small>drzwi wewnętrzne</small>		D4 <small>drzwi wewnętrzne</small>		D5 <small>drzwi wewnętrzne</small>		D6 <small>drzwi wewnętrzne</small>	
Schemat <small>skala 1:50</small>																
	wymiary w świetle muru [cm]	So	100	110	100	100	210	210	90	110	110	210	210	100	100	
	wymiary w świetle ościeżnicy	Ho	210	210	210	210	90	90	205	210	210	210	210	210	210	
		S	90	100	90	90	80	100	100	90	90	90	90	90	90	
	H	205	205	205	205	205	205	205	205	205	205	205	205	205		
rodzaj skrzydła	L	P	L	P	L	P	L	P	L	P	L	P	L	P		
parter		1		1		1		3		1		1		2		1
ogółem		1		1		1		3		1		1		2		1
uwagi	drzwi antywłamaniowe		drzwi antywłamaniowe				drzwi łazienkowe z kratką wentylacyjną o przekroju min. 0,022m ²		drzwi łazienkowe z kratką wentylacyjną o przekroju min. 0,022m ²		EI30		klasa odporności ogniowej : EI30		klasa odporności ogniowej : EI30	